

# Oil & Petroleum Supply Chain



## Oil & Petroleum Supply Chain

Hoses and hose assemblies - Expansion joints - Sheetings

[www.trelleborg.com/industrialhose](http://www.trelleborg.com/industrialhose)

# Trelleborg Fluid Handling Solutions

## **Trelleborg Fluid Handling Solutions is part of Trelleborg Industrial Solutions.**

With over 1000 employees and head office located in Clermont-Ferrand (France), Trelleborg Fluid Handling Solutions is a key leading player proposing high performance and optimal solutions for every situation with low and medium pressure Industrial Hose, Oil and Marine Hoses, Rubber Sheetting & Matting and Expansion Joint based on advanced polymer technology with production sites in France, Spain, Sweden and Brazil.

Trelleborg Fluid Handling Solutions offers a very large range of competitive products, solutions and services that meet your needs and requirements for all types of application for your different businesses.



### ► **Your Partner for Fluid Handling**

Trelleborg Fluid Handling Solutions is organized around 9 applications areas:

- **Oil and Gas**
- **Construction and Mining Equipment**
- **Energy**
- **Chemical, Pharma and Food**
- **Agriculture and Farms**
- **Environment and Cleaning Waste Water**
- **Processing Equipment and Machine Tools**
- **Industrial Transportation**
- **Life Science**



This enables better reactivity to adapt our offer to fast moving application or to design special solutions tailor-made for you. In all cases we follow closely legal requirements or standard evolutions.

### ► **Our logistics platform: availability, reactivity and reliability**


















Over 5000 different items are stored in our 3 logistic platforms in Clermont-Ferrand (France), Trelleborg (Sweden) and Izarra (Spain) to meet your need for immediate and reliable delivery.

### **In order to help you to accelerate the development of your business, our service list also covers**

- Compounding formulation
- Hose configuration modeling
- Finite element calculations
- Hose design
- Hose testing (pressure, bending, elongation resistance, ...)
- Hose certification (PED, ADR, REACH, ...)
- Handling and storage instructions
- Installation instruction and supports
- Hose inspection and refurbishment
- Hose failure analysis
- After sales support
- Training for sales team
- Training for assembly workshop operators



# Hose range

Product name/Advantages	ID mm	Temperature	Working pressure bar	Standard Approval
 <b>VOLUKLER/ VOLUKLER VR</b> → Good resistance to ageing. → Conductive inner tube.	16 to 25	- 25 to + 65 °C	16	EN 1360 EN 13483 Type 1
 <b>VOLUME</b> → Highly flexible. → Available in red or orange cover.	32 to 50	- 30 to + 55 °C	16	EN 1360 Type 1
 <b>PUMPADUKT D</b> → Can be cut to length as required.	19 to 200	- 40 to + 100 °C	16	EN 1761 EN 12115
 <b>BUTANE PROPANE E</b> → Highly flexible.	12.7 to 200	- 30 to + 100 °C	25	EN 1762 Type D/SD
 <b>TRELLEX OIL/CHEM</b> → Both black and white oil can be carried.	25 to 250	- 30 to + 100 °C	10/14	EN 13765 (Ex BS 5842)
 <b>TRELLOIL S/TRELLOIL D</b> → Highly flexible. → Good resistance to ageing.	25 to 100	- 30 to + 80 °C	10	-
 <b>PUMPADUKT S</b> → Very robust and flexible.	19 to 200	- 40 to + 100 °C	16	EN 12115 EN 1761
 <b>CHEMIKLER RANGE</b> → Available with EPDM UPE or FEP tubes. → Good mechanical resistance.	13 to 150	- 30 to + 100 °C	16	EN 12115
 <b>MAGDALA</b> → Can be coiled flat. → FKM tube available.	50 to 300	- 20 to + 82 °C	10/15	EN 1765 (Ex BS 1435) Type L10 L15
 <b>DOCKER</b> → Smooth inner tube. → FKM tube available. → Heavy duty.	75 to 300	- 20 to + 82 °C	15	EN 1765 (Ex BS 1435) Type S15
 <b>TRELLOIL S EC/TRELLOIL D EC</b> → Highly flexible. → Good resistance to ageing. → Conductive inner tube.	100 to 251	- 40 to + 100 °C	20	-
 <b>TRELLEFLOAT</b> → Floating hose.	100 to 125	- 20 to + 80 °C	20	-
 <b>CHEMIKLER EPDM</b> → Good chemical resistance. → Robust.	19 to 100	- 30 to + 100 °C	10	EN 12115
 <b>PETROVAST/S 2096/SUPERVAST</b> → Multipurpose hose.	9.5 to 51	Saturated steam: + 210 °C Superheated steam: + 230 °C	Steam: 18 bar Water: 60 bar	EN ISO 6134 Type 2, class A
 <b>AEROKLER/AEROKLER F</b> → Light weight, flexible and abrasion resistant hose.	19 to 100	- 40 to + 100 °C	20	EN 1529 ISO 1825
 <b>TRELLEX ROOF DRAIN</b> → 100 % aromatics resistance. → Natural negative buoyancy.	50 to 250	- 30 to + 100 °C	14	BS 5842
 <b>METAL HOSE</b> → Extreme temperatures.	6 to 400	- 200 to + 200 °C	10/14	EN 10380



# From downstream...



## Bunkering/Refinery

### Ship to shore

#### TRELLFLEX

Suction and discharge of a large number of aggressive or corrosive chemicals, chemical waste, and all petroleum products with aromatic content up to 100 %.



### Oil resistant grade

#### SHEETING & MATTING

Electrical insulation.  
Oil resistant flooring.  
Fire resistant matting.



### Offshore floating supply hose

#### TRELLFLOAT

Rough, self floating hose for ship to rig purpose, as supply hose. Suitable for most medias like oil, diesel, water, cement, brine, baryte etc.



### Ship to shore/bunkering

#### MAGDALA/DOCKER TRELLOIL S/D EC

Suction and/or discharge of petroleum products for dock or barge service.  
For refined products with aromatic up to 50 %.



### Bitumen loading/unloading

#### METAL HOSE

For loading/unloading bitumen tar, hot asphalt at 200 °C.



### LPG unloading

#### BUTANE PROPANE E

Discharge under pressure of petroleum products with aromatic content ≤ 50 %. LPG delivery.



### Accessories and services available on demand:

trolley, sling, rope lagging, insulating flange/gasket, dry break & safety break away couplings, floaters, inspections, etc.



# Storage



## Floating roof tank

### TRELLFLEX ROOF DRAIN


Removal of rain water from the roof of an external floating roof tank.



## Bottom loading

### AEROKLER - PUMPADUKT S TRELLFLEX OIL/VR

Loading of petroleum products with aromatic content up to 50 % and vapor recovery in bottom loading station.



## Tank truck

### PUMPADUKT - TRELLFLEX CHEMIKLER EPDM

Suction and discharge of petroleum products with aromatic content up to 50 %.  
Loading and unloading of boats and road or rail tankers. Fixed installations in various industries.



## Steam

### PETROVAST - S2096 SUPERVAST

For heavy duty industrial cleaning and circulation of saturated and superheated steam in heating systems.  
Used in the petrochemical, building, shipyard, and chemical industry.



## Expansion joint

### TEGUFLEX®

For all types of industrial applications, residential houses, industrial plants, industrial premises as well as heating and sanitary installations.  
Compensate for thermal elongation and misalignment. Isolate vibration, dampen noise and pressure surges coming from engines, pumps, turbines etc.



## Special features on demand:

dry break & safety break away couplings, colour sleeve, whipcheck, etc.



# To distribution...



## Domestic

### Tank truck

#### **PUMPADUKT - TRELLFLEX CHEMIKLER EPDM**

Suction and discharge of petroleum products with aromatic content up to 50 %.

Loading and unloading of boats and road or rail tankers. Fixed installations in various industries.

### Petrol pump station

#### **VOLUKLER/ VOLUKLER VR**

For equipment of petrol pumps: regular, super and unleaded petrol and diesel oil.

With or without vapor recovery system.

### Domestic fuel delivery

#### **VOLUDEC**


For hose reels on road tankers for metered delivery of household and automotive fuel.

### Domestic gas delivery

#### **BUTANE PROPANE E/E+**

For reels on road tankers for LPG delivery.

Discharge under pressure of petroleum products with aromatic content  $\leq 50$  %.



#### **Accessories on demand:**

dry break & safety break away couplings, swivel fittings, sleeves, nozzles, fittings, gaskets, etc.





## Refueling/Defueling

### AEROKLER C/F

Aircraft ground refuelling and/or defuelling with kerosene or petroleum fuel, aromatic content  $\leq 50\%$ .  
Fuel discharge under pressure.



## Expansion joint

### TEGUFLEX®

Flanged compensators used to:  
- isolate vibration,  
- dampen noise and pressure surges,  
and installed on board of aircraft refuellers/dispensing vehicles.



### Accessories on demand:

hose guard spring, abrasion rings, trolley, couplings, gaskets, etc.





BU Fluid Handling Solutions  
Trelleborg Industrie SAS  
ZI La Combaude - Rue de Chantemerle - CS 10725  
63050 Clermont-Ferrand cedex 2 France  
Tel +33 (0)4 73 25 81 00 - Fax +33 (0)4 73 25 82 17  
[tes.serviceclients@trelleborg.com](mailto:tes.serviceclients@trelleborg.com) - [www.trelleborg.com/industrialhose](http://www.trelleborg.com/industrialhose)  
SAS au capital de 9 909 450 € - RCS Clermont-Ferrand B 391 933 397  
SIRET 391 933 397 00013 - APE 2219Z - TVA FR 56 391 933 397